



S-H-P[®]
Quality Always Leads

Manufactured by:

SHARP HYDRO PRODUCTS

S.F. No.100/1A7, Near Thangamman Temple, Kalapatti, Coimbatore - 641 048. (TN) India.

E-mail : sharphydroproducts@gmail.com | Website : www.sharphydroproducts.com

FOR MORE DETAILS SCAN
WITH YOUR SMART PHONE



*Product may differ from the image. *IS for selective products only.



S-H-P[®]
Quality Always Leads

IS : 8472 : 1998



CM/L : 3400031



MONOBLOCK PUMPS | PRESSURE PUMPS

An ISO 9001:2015 Certified Company



S-H-P[®][©]
Quality Always Leads



Our Elegant Brands

S-H-P **Sharp Hydro**[®][©]

S-H-P **ULTRA SHARP**[®]

Aquarange[®]
Water pumps

SHARP[®]
grow

Forcee[®]
WATER PUMPS

CHAMP 50



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/kW	Flow Rate (LPH)	1800	1200	900	700	600	0
CHAMP 50	25x25	5.5 Kg	0.5/0.37	HEAD (m)	0	10	16	20	24	28

SHP 5050



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/kW	Flow Rate (LPH)	1800	1200	900	700	600	0
SHP 5050	25x25	5.5 Kg	0.5/0.37	HEAD (m)	0	10	16	20	24	28

SHP 5060



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/kW	Flow Rate (LPH)	2000	1700	1200	1000	700	0
SHP 5060	25x25	6.1 Kg	0.5/0.37	HEAD (m)	0	10	16	20	24	28

SHP 5065



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/kW	Flow Rate (LPH)	2000	1700	1200	1000	700	0
SHP 5065	25x25	6.1 Kg	0.5/0.37	HEAD (m)	0	10	16	20	24	28

SHP 5070



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/kW	Flow Rate (LPH)	3000	2700	1900	1700	1300	0
SHP 5070	25x25	8.3 Kg	0.5/0.37	HEAD (m)	0	10	18	20	24	34

SHP 1010



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

1.0 HP

Model	Pipe Size	Weight	HP/kW	Flow Rate (LPH)	3000	2700	1900	1700	1300	0
SHP 1010	25x25	8.6 Kg	1.0/0.75	HEAD (m)	0	10	18	20	24	38

OPERATING CONDITIONS

- Operating water temperature upto 50°C
- Max working pressure 5.5 kg/cm²
- Low power consumption
- Wide voltage operating range (180-240V)
- Direction of rotation : Anti clockwise viewed from driving end

OPERATING CONDITIONS

- Used in gardening, Farm house & building construction
- For lifting water overhead storage tanks
- Pressure booster systems
- Hotels, hospitals and fountains
- Water circulation in industries

MULTI STAGE CENTRIFUGAL BOOSTER PUMPS



FEATURES

- Stainless Steel Rotating Parts
- Multi-stage Impellers
- Higher Head per Stage
- Low Power Consumption
- Rugged Construction
- Thermal Protector
- Continuous Heavy Duty Motor

APPLICATIONS

- Industrial Use
- Multi Storied Buildings
- Residential Use
- Pressure Boosters
- Boiler Feed

MINI BOOSTER 2 L



- High Pressure Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

Voltage	230V, 50Hz
Power	0.5 HP / 0.37 kw
Size	25mm x 25mm

0.5 HP

MINI BOOSTER 24 L



- High Pressure Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

Voltage	230V, 50Hz
Power	0.5 HP / 0.37 kw
Size	25mm x 25mm

0.5 HP



- High Pressure Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems
- RO Water Pump
- Pressure Boosting Service
- Boiler Feed Water Pump
- Industrial Usage



Model	Pipe Size	HP/KW	Max. Pr Bar	Weight Kg.	Flow Rate (LPH)	0	1000	2000	3000	4000	5000	6000
MS 3A	25x25	0.8 / 0.6	2.0	15.0	Head (m)	27	24	20	15	10	5	0
MS 4A	25x25	1.0 / 0.75	3.0	16.0		36	30	24	20	15	10	0
MS 5A	25x25	1.5 / 1.2	4.0	17.0		45	38	30	25	20	15	0
MS 6A	25x25	2.0 / 1.5	5.0	18.0		54	46	38	30	25	20	0

About us



SHARP HYDRO PRODUCTS an ISO Certified Company to provide service and value to its customers from 2007. We offer a variety of products that can assist you with all your residential water needs.

Our vision is to satisfy the needs of people through the supply of quality products and services.

The factory is equipped with automatic assembly line to Bearing pressing, High voltage tester, End cover pressing, Mech seal pressing, High pressure testing unit, Finishing and Assembly jobs and has a trained man power and competent supervision.

Quality control is observed in each and every stage of manufacturing process.



An ISO 9001:2015 Certified Company



SHP 1012 (Cora)

Model	Pipe Size	Weight	HP/KW
SHP 1012	1 1/4"	16 Kg	1.0/0.75

Flow Rate (LPH)	6500	5800	5100	4000	2800	1200	0
HEAD (m)	10	20	30	40	50	60	65

SHP 1518 (Cora)

Model	Pipe Size	Weight	HP/KW
SHP 1518	1 1/4"	21 Kg	1.5/1.1

Flow Rate (LPH)	6800	6400	5900	5400	4700	4100	3300	2300	0
HEAD (m)	10	20	30	40	50	60	70	80	95

SHP 2024 (Cora)

Model	Pipe Size	Weight	HP/KW
SHP 2024	1 1/4"	27 Kg	2.0/1.5

Flow Rate (LPH)	4100	3700	3000	2300	1500	0
HEAD (m)	80	90	100	110	120	130

SHP R2024 (R3)

Flow Rate (LPH)	6600	6200	5500	5100	4600	4000	3400	2700	2000	0
HEAD (m)	10	30	50	70	90	110	130	150	170	200



SHP 1100



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

1.0 HP

Model	Pipe Size	Weight	HP/KW	Flow Rate (LPH)	3200	3000	2400	2100	1700	0
SHP 1100	25x25	9.3 Kg	1.0/0.75	HEAD (m)	0	10	16	20	24	40

SHP 1200



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

1.0 HP

Model	Pipe Size	Weight	HP/KW	Flow Rate (LPH)	3400	2800	2400	2200	1600	0
SHP 1200	25x25	10.5 Kg	1.0/0.75	HEAD (m)	0	10	16	20	26	50

CHAMP 100



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

1.0 HP

Model	Pipe Size	Weight	HP/KW	Flow Rate (LPH)	2800	2400	1600	1500	1300	0
SHP 1010	25x25	7.5 Kg	1.0/0.75	HEAD (m)	0	10	18	20	24	40

SHP 2200



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

1.5 HP

Model	Pipe Size	Weight	HP/KW	Flow Rate (LPH)	3800	2800	2400	2200	1600	0
SHP 2200	25x25	14.5 Kg	1.5/1.1	HEAD (m)	0	10	32	36	46	60

SHP SW50



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/KW	Flow Rate (LPH)	3000	2800	1800	1200	600	0
SHP SW50	25x25	15 Kg	0.5/0.37	HEAD (m)	0	16	20	22	24	28

SHP SW100



- Self Priming Pump
- Clear Water Pump
- Resi. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/KW	Flow Rate (LPH)	3000	2800	2400	1800	600	0
SHP SW 00	25x25	16 Kg	1.0/0.75	HEAD (m)	0	18	20	22	28	32

OPERATING CONDITIONS

- Operating water temperature upto 55°C
- Max working pressure 5.5 kg/cm²
- Low power consumption
- Wide voltage operating range (180-240V)
- Direction of rotation : Anti clockwise viewed from driving end

OPERATING CONDITIONS

- Used in gardening, Farm house & building construction
- For lifting water overhead storage tanks
- Pressure booster systems
- Hotels, hospitals and fountains
- Water circulation in industries

Self Priming Super Suction Pumps



SHP 5080



- Super Suction Pump
- Clear Water Pump
- Resl. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/KW	Flow Rate (LPH)	3000	2400	2200	1600	1200	0
SHP 5080	25x25	11 Kg	0.5/0.37	HEAD (m)	0	8	12	20	24	34

DMS



- Self Priming Pump
- Clear Water Pump
- Resl. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/KW	Flow Rate (LPH)	2800	2400	2200	1400	1100	0
DMS	25x25	17 Kg	0.5/0.37	HEAD (m)	0	6	10	20	24	32

Centrifugal Monoblock Pumps

MEGA 50



- Centrifugal Pump
- Clear Water Pump
- Resl. & Commercial
- Distribution Systems
- High Discharge

0.5 HP

Model	Pipe Size	Weight	HP/KW	Flow Rate (LPH)	6000	5500	3000	1500	0
MEGA 50	25x25	11 Kg	0.5/0.37	HEAD (m)	0	8	14	16	24

MEGA 100



- Centrifugal Pump
- Clear Water Pump
- Resl. & Commercial
- Distribution Systems
- High Discharge

1.0 HP

Model	Pipe Size	Weight	HP/KW	Flow Rate (LPH)	7200	6000	5500	3000	1500	0
MEGA 100	32x25	17 Kg	1.0/0.75	HEAD (m)	0	14	16	24	28	32

Openwell Submersible Pumps



MAX 50E



- Clear Water Pump
- Fountain
- Resl. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/KW
MAX 50E	25x25	14 Kg	0.5/0.37

Flow Rate (LPH)	6000	5500	4500	3500	2000	1000	0
HEAD (m)	0	4	8	12	16	18	20

MAX 50



- Clear Water Pump
- Fountain
- Resl. & Commercial
- Distribution Systems

0.5 HP

Model	Pipe Size	Weight	HP/KW
MAX 50	25x25	15 Kg	0.5/0.37

Flow Rate (LPH)	6000	5500	4500	3500	2000	1000	0
HEAD (m)	0	4	8	12	16	18	20

MAX 100E



- Clear Water Pump
- Fountain
- Resl. & Commercial
- Distribution Systems

1.0 HP

Model	Pipe Size	Weight	HP/KW
MAX 100E	25x25	16 Kg	1.0/0.75

Flow Rate (LPH)	6500	6000	5500	4500	3500	2000	1000	0
HEAD (m)	0	4	10	12	14	18	22	28

MAX 100



- Clear Water Pump
- Fountain
- Resl. & Commercial
- Distribution Systems

1.0 HP

Model	Pipe Size	Weight	HP/KW
MAX 100	25x25	17 Kg	1.0/0.75

Flow Rate (LPH)	6500	6000	5500	4500	3500	2000	1000	0
HEAD (m)	0	4	16	20	24	26	28	30

